

CavityTherm[®]

Built-in Full Fill Wall Insulation

CT/PIR-Flex

Insulation for
Full Fill Cavity-Wall

The built-in full fill cavity wall insulation shall be CavityTherm Flex by Xtratherm, including corner boards and ancillary detail components, comprising a rigid Polyisocyanurate (PIR) core manufactured to EN 13165 between low emissivity foil facings and Flexible Fleece to inner skin with engineered HIPS to outer skin. The CavityTherm Flex ___mm with a declared Lambda value of 0.021 W/mK (PIR) and 0.036 W/mK (Flexible Fleece) to achieve a U-Value of ___W/m2K for the wall element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause F30 150, F30 12

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

BS EN ISO 9001 Quality Management System
BS EN ISO 14001 Environmental Management System

Manufacturer

Xtratherm UK Limited

Holmewood Industrial Park, Holmewood
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

info@xtratherm.com

www.xtratherm.com

Xtratherm Limited

Liscarton Industrial Estate, Kells Road,
Navan, Co.Meath, Ireland, C15NP79

T +353 (0)46 906 6000

F +353 (0)46 906 6090

info@xtratherm.com

www.xtratherm.ie

Face size

1200 x 450 mm

Edge profile

Rebated all four edges

Thickness

125 mm / 150mm

Product reference

Xtratherm Thin-R CavityTherm Flex
Full Fill Cavity Wall Insulation

Other sizes available dependent on quantity & lead time.